



Panels

Nylofor Medium system is a complete high quality fencing system, which guarantees an extra long lifetime at a low cost.

Nylofor[®] Medium



BENEFITS

Extra long lifetime

The wire is galvanised, resistance welded and plastic coated with maximum adhesion. The coating technology of Betafence is state of the art and guarantees extra long lifetime.

Rigidity and quality

The panels are heavy welded mesh with rectangular meshes and horizontal reinforcements which give the panels a high rigidity. Nylofor Medium provides high quality at low cost.

Rapid and fault-free installation

All components are perfectly harmonised with each other and developed to give a professional quality fence, installed with maximum efficiency.

Complete system

The system consists of panels in various heights, square or Bekafix posts with a specific fixing system, adapted accessories and a wide assortment of innovative swing and sliding gates. Aesthetically pleasing and environmentally friendly.

Applications

The Nylofor Medium System is highly recommended for professional fencing of parks, office parks, shopping centres, lifestyle centres, sports grounds, schools, factories and warehouses.



Panels

The panels have a width of 2500 mm and are available in a range of heights: from 1030 to 2030 mm. The panels have vertical barbs of 30 mm at one side, the barbs can be placed at the top or at the bottom.

The horizontal reinforcements give the panels extra rigidity.

The meshes are 100 x 50 mm, as well as the reinforcements.

The wire diameter is 4,4 mm.



Posts and fixing

Bekafix Post System

The panels are fixed lateral on the posts with specific fixators made out of polyamide or metal (security). The welded tubular posts (70 x 44 mm), in H-shape are covered with a plastic cap.

Optional can also be chosen for square posts.

See Nylofor 3D.



Square post system

The panels are fixed on the front side of the posts by means of fixators and security bolts. The welded square tubular posts (60 x 60 x 1,50 mm) have inserts for fixing the panels with the fixators and are covered with a plastic cap.

Gates

The Nylofor Medium system is totally finished and safely equipped with high tech gates type Nylofor or Robusta: single and double gates, swing and sliding gates.

Coating techniques

Panels made out of galvanised wires. A pre-treatment process guarantees a perfect PVC-coating adhesion to the product surface.

The posts are in- and outside galvanised (min. coating 275g/m², both sides together), in accordance with SANS 10224-2. Afterwards an adhesion coating is applied and finally the posts are plastic coated (min. 60 micron).

Colours

Standard colours: green RAL 6005 or anthracite RAL 7021

Other colours on request

ASSORTMENT NYLOFOR MEDIUM

Fence height mm	Panels width x height mm	Number of reinforcements per panel	Post length mm	Bekafix posts		Square posts	
				Number of fixings per intermediate & corner post	Number of fixings per end post	Number of fixings per intermediate & end post	Number of fixings per corner post
1030	2500 x 1030	2	1500	4	2	3	6
1230	2500 x 1230	2	1700	4	2	4	8
1530	2500 x 1530	3	2000	6	3	4	8
1730	2500 x 1730	3	2200	6	3	5	10
2030	2500 x 2030	4	2600	8	4	6	12



Betafence South Africa (Pty) Ltd Distributors:
Impiwire



Postal Address:

P O Box 1848, George, 6530

Physical Address:

Foundry Street, George Industria

Phone: +27 (0)44 802 7301

Fax: +27 (0)44 802 7373 • www.impiwire.co.za